



TEST REPORT
IEC 60598-2-5
Luminaires
Part 2: Particular requirements
Section 5: Floodlights

Report Number.....: AOC250508001S

Date of issue.....: 2025-06-17

Total number of pages 58 pages

Name of Testing Laboratory preparing the Report.....: Shenzhen AOCE Electronic Technology Service Co., Ltd
Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China

Applicant's name.....: SBC LIGHTING SDN BHD

Address.....: No,15 JALAN SKI 4/KU7, KAWASAN INDUSTRI HITECH,SUNGAI KAPAR INDAH,42200, KAPAR,SELANGOR D.E,MALAYSIA

Test specification:

Standard.....: ☒ IEC 60598-2-5:2015
☒ IEC 60598-1:2020
☒ European Group Differences And National Differences

Test procedure.....: Type testing

Non-standard test method.....: N/A

Test Report Form No.....: IEC60598_2_5F

Test Report Form(s) Originator.....: Intertek Semko AB

Master TRF.....: Dated 2018-04-06

Copyright © 2018 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

General disclaimer:

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the Testing Laboratory, responsible for this Test Report.

Test item description..... :	LED Flood Light	
Trade Mark..... :		
Manufacturer..... :	SBC LIGHTING SDN BHD No.15 JALAN SKI 4/KU7, KAWASAN INDUSTRI HITECH,SUNGAI KAPAR INDAH,42200, KAPAR,SELANGOR D.E,MALAYSIA	
Model/Type reference..... :	See Model List	
Ratings..... :	220-277 V~, 50/60 Hz, 1800 W, Class I, IP 66, ta:50°C	
Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):		
☒	Testing Laboratory:	Shenzhen AOCE Electronic Technology Service Co., Ltd
	Testing location/ address..... :	Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China
	Tested by (name, function, signature)..... :	ZhiCong Xian Technical Engineer <i>ZhiCong Xian</i>
	Approved by (name, function, signature)... :	Robin Liu Technical Manager <i>Robin. Liu</i>
☐	Testing procedure: CTF Stage 1:	N/A
	Testing location/ address..... :	
	Tested by (name, function, signature)..... :	
	Approved by (name, function, signature)... :	
☐	Testing procedure: CTF Stage 2:	N/A
	Testing location/ address..... :	
	Tested by (name + signature)..... :	
	Witnessed by (name, function, signature).. :	
	Approved by (name, function, signature)... :	
☐	Testing procedure: CTF Stage 3:	N/A
☐	Testing procedure: CTF Stage 4:	N/A
	Testing location/ address..... :	
	Tested by (name, function, signature)..... :	
	Witnessed by (name, function, signature).. :	
	Approved by (name, function, signature)... :	
	Supervised by (name, function, signature) :	

Tel: (86)755-85277785

Fax: (86)755-23705230

E-mail: postmaster@aoc-cert.comWebsite: [Http://www.aoc-cert.com](http://www.aoc-cert.com)

TRF No. IEC60598_2_5F

List of Attachments (including a total number of pages in each attachment):**Attachment No.1:** European Group Differences And National Differences.**Attachment No.2:** Clause 13 of EN IEC 62031**Attachment No.3:** IEC TR 62778**Attachment No.4:** Photo document.**Summary of testing:****Tests performed (name of test and test clause):**

- EN 60598-2-5:2015
- EN IEC 60598-1:2021+A11:2022
- Clause 13 of EN IEC 62031:2020+A11:2021
- IEC TR 62778:2014
- EN 62493:2015+A1:2022

Testing location:

Shenzhen AOCE Electronic Technology Service Co., Ltd
 Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China

Summary of compliance with National Differences:

European Group Differences And National Differences.

☒ **The product fulfils the requirements of EN 60598-2-5:2015 & EN IEC 60598-1:2021+A11:2022**

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.

	VL-FL-G4.5-1800W 6500K
	220-277V~50/60Hz λ 0.95
	ta 50°C IK08 CLASS I
IP66 CE  MADE IN MALAYSIA	

Remark:

1. The marking plate of others are identical with model VL-FL-G4.5-1800W, except the model number and rated power.
2. The above marking is the minimum requirements required by the safety standard. For the final production, the additional mark which do not give rise to misunderstanding may be added.
3. The height of graphical symbols shall not be less than 5 mm, the height of letters shall not be less than 2 mm

Test item particulars..... :	
Classification of installation and use..... :	Fixed luminaire
Supply Connection..... :	Supply cord
..... :	
Possible test case verdicts:	
- test case does not apply to the test object..... :	N/A
- test object does meet the requirement..... :	P (Pass)
- test object does not meet the requirement..... :	F (Fail)
Testing..... :	
Date of receipt of test item..... :	2025-04-24
Date (s) of performance of tests..... :	2025-04-24 to 2025-06-17
General remarks:	
The tested sample(s) and the sample information are provided by the client. "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Note: EN Group Differences together with National Differences and Special National Conditions, if any, are in the Appendix to the main body of this TRF. Throughout this report a ☐ comma / ☒ point is used as the decimal separator. The test report only allows to be revised only within the report defined retention period unless standard or regulation was withdrawn or invalid. When determining for test conclusion, measurement uncertainty of tests has been considered. Clause numbers between brackets refer to clauses in IEC 60598-1. Note: clauses marked “*” not included in CNAS scope.	
Manufacturer's Declaration per sub-clause 4.2.5 of IEC 60598-1:	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided.. :	☐ Yes ☒ Not applicable
When differences exist; they shall be identified in the General product information section.	
Name and address of factory (ies)..... : Same as manufacturer	

General product information and other remarks:

The manufacturer/ Importer has to ensure the appliance placing on the EU market conforms to the applicable EU directives which provide the affixing of the CE marking, such as LVD, EMC, RoHS, ErP, and so on. According to the EU directives which have been aligned with EU NLF (new legislative framework), both of manufacturer and importer's name and address shall be affixed on the product or, where that is not possible, on its packaging or in a document accompanying the product before the product is placed on the EU market. The product covered in this report is class I food light with non-user replaceable light sources for indoor and outdoor use. Max, mounting height is 70m. Model list details see below:

Model	Rating	LED Driver	LED Qty.
VL-VL-G4.5-300W	AC 220-277V, 50/60Hz, 300W	N7-240M260A12 2pcs 600FGH420C 1pc	2835: (12C6B+16C7B)×2+(8C7B+20C8B) ×2 3030: (26C4B+16C5B)×2+(36C5B+6C6B)×2 2424: (68C2B+16C3B)×2+36C2B+48C3B)×2
VL-VL-G4.5-350W	AC 220-277V, 50/60Hz, 350W	N7-240M260A12 2pcs 600FGH420C 1pc	
VL-VL-G4.5-400W	AC 220-277V, 50/60Hz, 400W	N7-240M260A12 2pcs 600FGH420C 1pc	
VL-VL-G4.5-450W	AC 220-277V, 50/60Hz, 450W	N7-240M260A12 2pcs 600FGH420C 1pc	
VL-VL-G4.5-500W	AC 220-277V, 50/60Hz, 500W	N7-240M260A12 2pcs 600FGH420C 1pc EUM-480S280MG 1pc EUM-480S280BG 1pc EUM-680S350MG 1pc EUM-680S350BG 1pc S6-600D360 1pc S6-600R360 1pc	3030: 816pcs or 810 pcs; or 2835: 816pcs or 810pcs or 3535: 240pcs; or 2424: 240pcs:
VL-VL-G4.5-600W	AC 220-277V, 50/60Hz, 600W	EUM-680S350MG 1pc EUM-680S350BG 1pc 600FGH420C 1pc S6-600D360 1pc S6-600R360 1pc	3030: 816pcs or 810 pcs; or 2835: 816pcs or 810pcs or 3535: 240pcs; or 2424: 240pcs:
VL-VL-G4.5-800W	AC 220-277V, 50/60Hz, 800W	EUM-880S420MG 1pc	
VL-VL-G4.5-1000W	AC 220-277V, 50/60Hz, 1000W	EUM-480S280MG 2pcs	
		EUM-480S280BG 2pcs	
		EUM-680S350MG 2pcs EUM-680S350BG	

		2pcs	
		S6-1K2D500 1pc	
		S6-1K2R500 1pc	
VL-VL-G4.5-1200W	AC 220-277V, 50/60Hz, 1200W	EUM-680S350MG 2pcs	3030: 1632pcs or 1620pcs or 2835: 1632pcs or 1620pcs or 3535: 480pcs; or 2424: 480pcs:
		EUM-680S350BG 2pcs	
		S6-1K2D500 1pc	
		S6-1K2R500 1pc	
VL-VL-G4.5-1500W	AC 220-277V, 50/60Hz, 1500W	1800STH500C-xxxxx 1pc	2835: 1632pcs or 1620pcs or 3535: 480pcs; or 2424: 480pcs:
		HDE-1800STH500C 1pc	
		EUM-880S420MG 2pcs	
VL-VL-G4.5-1600W	AC 220-277V, 50/60Hz, 1600W	EUM-880S420MG 2pcs	
VL-VL-G4.5-1500W	AC 220-277V, 50/60Hz, 1500W	EUM-480S280MG 3pcs	3030: 2448pcs or 2430pcs; or 2835: 2448pcs or 2430pcs; or 3535: 720pcs; or 2424: 720pcs:
		EUM-480S280BG 3pcs	
		EUM-680S350MG 3pcs	
		EUM-680S350BG 3pcs	
		EUCO-1K5140GLA 1pc	
		EUCO-1K5140GDA 1pc	
		S6-1K8D500 1pc	
		S6-1K8R500 1pc	
		1800STH500C-xxxxx 1pc	
		HDE-1800STH500C 1pc	
VL-VL-G4.5-1800W	AC 220-277V, 50/60Hz, 1800W	EUM-680S350MG 3pcs	3030: 2448pcs or 2430pcs; or 2835: 2448pcs or 2430pcs; or 3535: 720pcs; or 2424: 720pcs:
		EUM-680S350BG 3pcs	
		S6-1K8D500 1pc	
		S6-1K8R500 1pc	
		1800STH500C-xxxxx 1pc	
		HDE-1800STH500C 1pc	
Remark: Covers all 2700K,3000K,3500K,4000K,4500K,5000K,5700K,6000K, 6500K. indicates CCT.			

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
5.4 (0+2)	CLASSIFICATION OF LUMINAIRES		P
5.4 (0)	General requirements and tests		—
5.4 (0.3)	More sections applicable.....:	Yes ☐ No ☒ Section/s:	—
5.4 (0.5)	Components	(see Annex 1)	—
5.4 (0.7)	Information for luminaire design in light sources standards		—
5.4 (0.7.2)	Light source safety standard	IEC 62031	—
	Luminaire design in the light source safety standard		—
5.4 (2)	Classification of luminaires		—
5.4 (2.2)	Type of protection	Class I	P
5.4 (2.3)	Degree of protection.....:	IP 66	—
5.4 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces.....:	Yes ☒ No ☐	—
5.4 (2.5)	Luminaire for normal use	Yes ☒ No ☐	—
	Luminaire for rough service	Yes ☐ No ☒	—

5.5 (3)	MARKING		P
5.5 (3.2)	Mandatory markings		P
	Position of the marking		P
	Format of symbols/text		P
5.5 (3.3)	Additional information		P
	Language of instructions		P
5.5 (3.3.1)	Combination luminaires		N/A
5.5 (3.3.2)	Nominal frequency in Hz		P
5.5 (3.3.3)	Operating temperature		N/A
5.5 (3.3.5)	Wiring diagram		N/A
5.5 (3.3.6)	Special conditions		N/A
5.5 (3.3.7)	Metal halide lamp luminaire – warning		N/A
5.5 (3.3.8)	Limitation for semi-luminaires		N/A
5.5 (3.3.9)	Power factor and supply current		P
5.5 (3.3.10)	Suitability for use indoors		N/A
5.5 (3.3.11)	Luminaires with remote control		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
5.5 (3.3.12)	Clip-mounted luminaire – warning		N/A
5.5 (3.3.13)	Specifications of protective shields		N/A
5.5 (3.3.14)	Symbol for nature of supply		P
5.5 (3.3.15)	Rated current of socket outlet		N/A
5.5 (3.3.16)	Rough service luminaire		N/A
5.5 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments		P
5.5 (3.3.18)	Non-ordinary luminaires with PVC cable		N/A
5.5 (3.3.19)	Protective conductor current in instruction if applicable		N/A
5.5 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		N/A
5.5 (3.3.21)	Non-replaceable and non-user replaceable light sources information provided		P
5.5 (3.3.22)	Controllable luminaires, classification of insulation provided		N/A
5.5 (3.3.23)	Luminaire without controlgear provided with necessary information for selection of appropriate component		N/A
5.5 (3.3.24)	If not supplied with terminal block, information on the packaging		P
5.5 (3.4)	Test with water		P
	Test with hexane		P
	Legible after test		P
	Label attached		P
5.5 (-)	Additional information if applicable		P
	a) Operation position		P
	b) Weight and dimensions		P
	c) Maximum protected area		P
	d) Limitation of use indoors and/or outdoor		P
	e) Maximum mounting height if ≤ 5 m		N/A

5.6 (4)	CONSTRUCTION		P
5.6 (4.2)	Components replaceable without difficulty		P
5.6 (4.3)	Wireways smooth and free from sharp edges		P

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
5.6 (4.4)	Lampholders		N/A
5.6 (4.4.1)	Integral lampholder		N/A
5.6 (4.4.2)	Wiring connection		N/A
5.6 (4.4.3)	Lampholder for end-to-end mounting		N/A
5.6 (4.4.4)	Positioning		N/A
	- pressure test (N)		—
	After test the lampholder comply with relevant standard sheets and show no damage		N/A
	After test on single-capped lampholder the lampholder have not moved from its position and show no permanent deformation		N/A
	- bending test (N)		—
	After test the lampholder have not moved from its position and show no permanent deformation		N/A
5.6 (4.4.5)	Peak pulse voltage		N/A
5.6 (4.4.6)	Centre contact		N/A
5.6 (4.4.7)	Parts in rough service luminaires resistant to tracking		N/A
5.6 (4.4.8)	Lamp connectors		N/A
5.6 (4.4.9)	Caps and bases correctly used		N/A
5.6 (4.4.10)	Light source for lampholder or connection according IEC 60061 not connected another way		N/A
5.6 (4.5)	Starter holders		N/A
	Starter holder in luminaires other than class II		N/A
	Starter holder class II construction		N/A
5.6 (4.6)	Terminal blocks		N/A
	Tails		N/A
	Unsecured blocks		N/A
5.6 (4.7)	Terminals and supply connections		P
5.6 (4.7.1)	Contact to metal parts		N/A
5.6 (4.7.2)	Test 8 mm live conductor		N/A
	Test 8 mm earth conductor		N/A
5.6 (4.7.3)	Terminals for supply conductors		P
5.6 (4.7.3.1)	Welded method and material		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	- stranded or solid conductor		N/A
	- spot welding		N/A
	- welding between wires		N/A
	- Type Z attachment		N/A
	- mechanical test according to 15.6.2		N/A
	- electrical test according to 15.6.3		N/A
	- heat test according to 15.6.3.2.3 and 15.6.3.2.4		N/A
5.6 (4.7.4)	Terminals other than supply connection		N/A
5.6 (4.7.5)	Heat-resistant wiring/sleeves		N/A
5.6 (4.7.6)	Multi-pole plug		N/A
	- test at 30 N		N/A
5.6 (4.8)	Switches		N/A
	- adequate rating		N/A
	- adequate fixing		N/A
	- polarized supply		N/A
	- compliance with IEC 61058-1 for electronic switches		N/A
5.6 (4.9)	Insulating lining and sleeves		N/A
5.6 (4.9.1)	Retainment		N/A
	Method of fixing.....:		N/A
5.6 (4.9.2)	Insulated linings and sleeves:		N/A
	Resistant to a temperature > 20 °C to the wire temperature or		N/A
	a) & c) Insulation resistance and electric strength		N/A
	b) Ageing test. Temperature (°C).....:		N/A
5.6 (4.10)	Double or reinforced insulation		N/A
5.6 (4.10.1)	No contact, mounting surface – accessible metal parts – wiring of basic insulation		N/A
	Safe installation fixed luminaires		N/A
	Capacitors and switches		N/A
	Interference suppression capacitors according to IEC 60384-14		N/A
5.6 (4.10.2)	Assembly gaps:		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	- not coincidental		N/A
	- no straight access with test probe		N/A
5.6 (4.10.3)	Retainment of insulation:		N/A
	- fixed		N/A
	- unable to be replaced; luminaire inoperative		N/A
	- sleeves retained in position		N/A
	- lining in lampholder		N/A
5.6 (4.10.4)	Protective impedance device		N/A
	Double or reinforced insulation bridged by appropriate and at least two resistors or two Y2 capacitors or one Y1 capacitor		N/A
	Y1 or Y2 capacitors comply with IEC 60384-14		N/A
	Resistors comply with test (a) in 14.1 of IEC 60065		N/A
5.6 (4.11)	Electrical connections and current-carrying parts		P
5.6 (4.11.1)	Contact pressure		P
5.6 (4.11.2)	Screws:		N/A
	- self-tapping screws		N/A
	- thread-cutting screws		N/A
5.6 (4.11.3)	Screw locking:		N/A
	- spring washer		N/A
	- rivets		N/A
5.6 (4.11.4)	Material of current-carrying parts		P
5.6 (4.11.5)	No contact to wood or mounting surface		P
5.6 (4.11.6)	Electro-mechanical contact systems		N/A
5.6 (4.12)	Screws and connections (mechanical) and glands		P
5.6 (4.12.1)	Screws not made of soft metal		P
	Screws of insulating material		N/A
	Torque test: torque (Nm); part.....:	0.5 Nm, Fixing screw of the earthing	P
	Torque test: torque (Nm); part.....:		N/A
	Torque test: torque (Nm); part.....:		N/A
	Torque test: torque (Nm); part.....:		N/A
	Torque test: torque (Nm); part.....:		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
5.6 (4.12.2)	Screws with diameter < 3 mm screwed into metal		N/A
5.6 (4.12.4)	Locked connections:		P
	- fixed arms; torque (Nm)..... :	2.5	P
	- lampholder; torque (Nm)..... :		N/A
	- push-button switches; torque 0,8 Nm..... :		N/A
5.6 (4.12.5)	Screwed glands; force (Nm)..... :		N/A
5.6 (4.13)	Mechanical strength		P
5.6 (4.13.1)	Impact tests:		P
	- fragile parts; energy (Nm)..... :	0.5	P
	- other parts; energy (Nm)..... :	0.7	P
	1) live parts		P
	2) linings		N/A
	3) protection		P
	4) covers		P
5.6 (4.13.2)	Metal parts have adequate mechanical strength		P
5.6 (4.13.3)	Straight test finger		P
5.6 (4.13.4)	Rough service luminaires		N/A
	- IP54 or higher		N/A
	a) fixed		N/A
	b) hand-held		N/A
	c) delivered with a stand		N/A
	d) for temporary installations and suitable for mounting on a stand		N/A
+	Tumbling barrel		N/A
5.6 (4.14)	Suspensions, fixings and means of adjusting		P
5.6 (4.14.1)	Mechanical load:		P
	A) four times the weight		P
	B) torque 2,5 Nm		P
	C) bracket arm; bending moment (Nm)..... :		P
	D) load track-mounted luminaires		N/A
	E) clip-mounted luminaires, glass-shelve. Thickness (mm)		N/A
	Metal rod. diameter (mm)		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	Fixed luminaire or independent control gear without fixing devices		N/A
5.6 (4.14.2)	Load to flexible cables		N/A
	Mass (kg)		—
	Stress in conductors (N/mm ²)		N/A
	Mass (kg) of semi-luminaire		N/A
	Bending moment (Nm) of semi-luminaire		N/A
5.6 (4.14.3)	Adjusting devices:		P
	- flexing test; number of cycles.....		P
	- strands broken.....		P
	- electric strength test afterwards		P
5.6 (4.14.4)	Telescopic tubes: cords not fixed to tube; no strain on conductors		N/A
5.6 (4.14.5)	Guide pulleys		N/A
5.6 (4.14.6)	Strain on socket-outlets		N/A
5.6 (4.15)	Flammable materials		P
	- glow-wire test 650°C.....	See Test Table 5.15 (13.3.2)	N/A
	- spacing ≥30 mm		N/A
	- screen withstanding test of 13.3.1		N/A
	- screen dimensions		N/A
	- no fiercely burning material		P
	- thermal protection		N/A
	- electronic circuits exempted		N/A
5.6 (4.15.2)	Luminaires made of thermoplastic material with lamp control gear		N/A
	a) construction		N/A
	b) temperature sensing control		N/A
	c) surface temperature		N/A
5.6 (4.16)	Luminaires for mounting on normally flammable surfaces		P
	No lamp control gear.....	(compliance with Section 12)	N/A
	Provided with adaptor for a track meet the requirements for direct mounting on normally flammable surfaces		N/A
5.6 (4.16.1)	Lamp control gear spacing:		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	- spacing 35 mm		N/A
	- spacing 10 mm		N/A
5.6 (4.16.2)	Thermal protection:		N/A
	- in lamp control gear		N/A
	- external		N/A
	- fixed position		N/A
	- temperature marked lamp control gear		N/A
5.6 (4.16.3)	Design to satisfy the test of 12.6	(see clause 12.6)	N/A
5.6 (4.17)	Drain holes		N/A
	Clearance at least 5 mm		N/A
5.6 (4.18)	Resistance to corrosion		P
5.6 (4.18.1)	- rust-resistance		P
5.6 (4.18.2)	- season cracking in copper		N/A
5.6 (4.18.3)	- corrosion of aluminium		P
5.6 (4.19)	Ignitors compatible with ballast		N/A
5.6 (4.20)	Rough service vibration		N/A
5.6 (4.21)	Protective shield		P
5.6 (4.21.1)	Shield fitted if tungsten halogen lamps or metal halide lamps		N/A
	Shield of glass if tungsten halogen lamps		N/A
5.6 (4.21.2)	Particles from a shattering lamp not impair safety		P
5.6 (4.21.3)	No direct path		N/A
5.6 (4.21.4)	Impact test on shield		N/A
	Glow-wire test on lamp compartment.....:	See Test Table 5.15 (13.3.2)	N/A
5.6 (4.22)	Attachments to lamps not cause overheating or damage		N/A
5.6 (4.23)	Semi-luminaires comply Class II		N/A
5.6 (4.24)	Photobiological hazards		P
5.6 (4.24.1)	No excessive UV radiation if tungsten halogen lamps and metal halide lamps (Annex P)		N/A
5.6 (4.24.2)	Retinal blue light hazard		P
	Class of risk group assessed according to IEC/TR 62778		—
	Luminaires with E_{thr} :		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	a) Fixed luminaires		N/A
	- distance x m, borderline between RG1 and RG2....:		N/A
	- marking and instruction according 3.2.23		N/A
	b) Portable and handheld luminaires		N/A
	- marking according 3.2.23 if RG1 exceeded at 200 mm according to IEC/TR 62778		N/A
	Portable luminaires for children IEC 60598-2-10 and Mains socket outlet nightlights IEC 60598-2-12 not exceed RG1 at 200 mm according to IEC/62778		N/A
5.6 (4.25)	Mechanical hazard		P
	No sharp point or edges		P
5.6 (4.26)	Short-circuit protection		N/A
5.6 (4.26.1)	Adequate means of uninsulated accessible SELV parts		N/A
5.6 (4.26.2)	Short-circuit test with test chain according 4.26.3		N/A
	Test chain not melt through		N/A
	Test sample not exceed values of Table 12.1 and 12.2		N/A
5.6 (4.27)	Terminal blocks with integrated screwless earthing contacts		N/A
	Test according Annex V		N/A
	Pull test of terminal fixing (20 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Pull test of mechanical connection (50 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Voltage drop test, resistance < 0,05 Ω		N/A
5.6 (4.28)	Fixing of thermal sensing control		N/A
	Not plug-in or easily replaceable type		N/A
	Reliably kept in position		N/A
	No adhesive fixing if UV radiations from a lamp can degrade the fixing		N/A
	Not outside the luminaire enclosure		N/A
	Test of adhesive fixing:		N/A
	Max. temperature on adhesive material ($^{\circ}\text{C}$):		—
	100 cycles between t min and t max		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	Temperature sensing control still in position		N/A
5.6 (4.29)	Luminaires with non-replaceable light source		N/A
	Not possible to replace light source		N/A
	Live part not accessible after parts have been opened by hand or tools		N/A
5.6 (4.30)	Luminaires with non-user replaceable light source		P
	If protective cover provide protection against electric shock and marked with "caution, electric shock risk" symbol:		P
	Minimum two fixing means		P
5.6 (4.31)	Insulation between circuits		P
	Circuits insulated from LV supply fulfil requirements according 4.31.1 – 4.31.3		P
	Controllable luminaires requiring same level of insulation for all components, the insulation between control terminals and LV supply fulfil requirements according 4.31.1 – 4.31.3		N/A
5.6 (4.31.1)	SELV circuits		P
	Used SELV source		P
	Voltage ≤ ELV		P
	Insulating of SELV circuits from LV supply		N/A
	Insulating of SELV circuits from other non SELV circuits		N/A
	Insulating of SELV circuits from FELV		N/A
	Insulating of SELV circuits from other SELV circuits		N/A
	SELV circuits insulated from accessible parts according Table X.1		P
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Plugs and socket-outlets does not have protective conductor contact		N/A
5.6 (4.31.2)	FELV circuits		N/A
	Used FELV source		N/A
	Voltage ≤ ELV		N/A
	Insulating of FELV circuits from LV supply		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	FELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Socket-outlets does not have protective conductor contact		N/A
5.6 (4.31.3)	Other circuits		P
	Other circuits insulated from accessible parts according Table X.1		P
	Class II construction with equipotential bonding for protection against indirect contacts with live parts:		N/A
	- conductive parts are connected together		N/A
	- test according 7.2.3		N/A
	- conductive part not cause an electric shock in case of an insulation fault		N/A
	- equipotential bonding in master/slave applications		N/A
	- master luminaire provided with terminal for accessible conductive parts of slave luminaires		N/A
	- slave luminaire constructed as class I		N/A
5.6 (4.32)	Overvoltage protective devices		N/A
	Comply with IEC 61643-11		N/A
	External to controlgear and connected to earth:		N/A
	- only in fixed luminaires		N/A
	- only connected to protective earth		N/A
5.6.1 (-)	At least IPX3 if for outdoor use	IP 66	P
5.6.2 (-)	Lampholder brackets and lamp supports		N/A
5.6.3 (-)	Adjusting means		P
5.6.4 (-)	Controlling components		N/A
5.6.5 (-)	Fixing device		P
	Wind force test		P
5.6.6 (-)	Locking of angular adjustment		P
5.6.7 (-)	Vibration resistance		P
5.6.8 (-)	Requirement on glass cover if mounting height > 5		P

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	m		
	Method of protection		—

5.7 (11)	CREEPAGE DISTANCES AND CLEARANCES		P
5.7 (11.2.1)	Impulse withstand category (Normal category II)	Category II ☒ Category III ☐	—
	Category III according Annex U		N/A
	Protected against pollution, reduced creepage and clearance according Annex P of IEC 61347-1		N/A
5.7 (11.2.2)	Creepage distances for frequency up to 30 kHz	See Test Table 5.7 (11.2) I	P
	Creepage distances for frequency over 30 kHz:		N/A
	- Controlgear marked with $\hat{U}_{OUT}$ and f_{UOUT} according IEC 61347-1, clause 7.1, item w	See Test Table 5.7 (11.2) II	N/A
	- Requirements according IEC 60664-4 for controlgear not covered by IEC 61347	See Test Table 5.7 (11.2) II	N/A
5.7 (11.2.3)	Clearances for frequency up to 30 kHz	See Test Table 5.7 (11.2) I	P
	Clearances distances for frequency over 30 kHz:		N/A
	- Controlgear marked with U_P	See Test Table 5.7 (11.2) II	N/A
	- Requirements according IEC 60664-4 for controlgear not covered by IEC 61347	See Test Table 5.7 (11.2) II	N/A

5.8 (7)	PROVISION FOR EARTHING		P
5.8 (7.2.1 + 7.2.3)	Accessible metal parts		P
	Metal parts in contact with supporting surface		P
	Resistance < 0,5 Ω:		P
	Self-tapping screws used		N/A
	Thread-forming screws		N/A
	Thread-forming screw used in a grove		N/A
	Earth makes contact first		P
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
	Protective earthing of the luminaire not via built-in control gear		P
5.8 (7.2.2 + 7.2.3)	Earth continuity in joints, etc.		P

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
5.8 (7.2.4)	Locking of clamping means		P
	Compliance with 4.7.3		P
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
5.8 (7.2.5)	Earth terminal integral part of connector socket		N/A
5.8 (7.2.6)	Earth terminal adjacent to mains terminals		N/A
5.8 (7.2.7)	Electrolytic corrosion of the earth terminal		P
5.8 (7.2.8)	Material of earth terminal		P
	Contact surface bare metal		P
5.8 (7.2.10)	Class II luminaire for looping-in		N/A
	Double or reinforced insulation to functional earth		N/A
5.8 (7.2.11)	Earthing core coloured green-yellow		P
	Length of earth conductor		P

5.9 (14)	SCREW TERMINALS		N/A
	Separately approved; component list	(see Annex 1)	N/A
	Part of the luminaire	(see Annex 3)	N/A

5.9 (15)	SCREWLESS TERMINALS AND ELECTRICAL CONNECTIONS		N/A
	Separately approved; component list.....:	(see Annex 1)	N/A
	Part of the luminaire.....:	(see Annex 4)	N/A

5.10 (5)	EXTERNAL AND INTERNAL WIRING		P
5.10 (5.2)	Supply connection and external wiring		P
5.10 (5.2.1)	Means of connection.....:		P
	Outdoor luminaire has not PVC insulated external wiring if not class III or SELV ≤ 25 V a.c./60 V d.c. or protected from outdoor environment		N/A
5.10 (5.2.2)	Type of cable.....:		P
	Nominal cross-sectional area (mm ²).....:		P
	Cables equal to IEC 60227 or IEC 60245		P
5.10 (5.2.3)	Type of attachment, X, Y or Z		P
5.10 (5.2.5)	Type Z not connected to screws		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
5.10 (5.2.6)	Cable entries:		P
	- suitable for introduction		P
	- adequate degree of protection		P
5.10 (5.2.7)	Cable entries through rigid material have rounded edges		P
5.10 (5.2.8)	Insulating bushings:		N/A
	- suitably fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- tubes or guards made of insulating material		N/A
5.10 (5.2.9)	Locking of screwed bushings		N/A
5.10 (5.2.10)	Cord anchorage:		P
	- covering protected from abrasion		P
	- clear how to be effective		P
	- no mechanical or thermal stress		P
	- no tying of cables into knots etc.		P
	- insulating material or lining		N/A
5.10 (5.2.10.1)	Cord anchorage for type X attachment:		N/A
	a) at least one part fixed		N/A
	b) types of cable		N/A
	c) no damaging of the cable		N/A
	d) whole cable can be mounted		N/A
	e) no touching of clamping screws		N/A
	f) metal screw not directly on cable		N/A
	g) replacement without special tool		N/A
	Glands not used as anchorage		N/A
	Labyrinth type anchorages		N/A
5.10 (5.2.10.2)	Adequate cord anchorage for type Y and type Z attachment		P
5.10 (5.2.10.3)	Tests:		P
	- impossible to push cable; unsafe		P

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	- pull test: 25 times; pull (N)..... :		P
	- torque test: torque (Nm)..... :		P
	- displacement ≤ 2 mm		P
	- no movement of conductors		P
	- no damage of cable or cord		P
	- function independent of electrical connection		P
5.10 (5.2.11)	External wiring passing into luminaire		P
5.10 (5.2.12)	Looping-in terminals		N/A
5.10 (5.2.13)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		P
5.10 (5.2.14)	Mains plug same protection		N/A
	Class III luminaire plug		N/A
	No unsafe compatibility		N/A
5.10 (5.2.16)	Appliance inlets (IEC 60320)		N/A
	Installation couplers (IEC 61535)		N/A
	Other appliance inlet or connector according relevant IEC standard		N/A
5.10 (5.2.17)	No standardized interconnecting cables properly assembled		N/A
5.10 (5.2.18)	Used plug in accordance with		N/A
	- IEC 60083		N/A
	- other standard		N/A
5.10 (5.3)	Internal wiring		P
5.10 (5.3.1)	Internal wiring of suitable size and type		P
	Through wiring		N/A
	- not delivered/ mounting instruction		N/A
	- factory assembled		N/A
	- socket outlet loaded (A)..... :		N/A
	- temperatures..... :	(see Annex 2)	N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	Green- yellow for earth only		N/A
5.10 (5.3.1.1)	Internal wiring connected directly to fixed wiring		N/A
	Cross-sectional area (mm ²)..... :		N/A
	Insulation thickness (mm) :		N/A
	Extra insulation added where necessary		N/A
5.10 (5.3.1.2)	Internal wiring connected to fixed wiring via internal current-limiting device		P
	Cross-sectional area (mm ²)..... :	(see Annex 1)	P
5.10 (5.3.1.3)	Double or reinforced insulation for class II		N/A
5.10 (5.3.1.4)	Conductors without insulation		N/A
5.10 (5.3.1.5)	SELV current-carrying parts		N/A
5.10 (5.3.1.6)	Insulation thickness other than PVC or rubber		N/A
5.10 (5.3.2)	Sharp edges etc.		P
	No moving parts of switches etc.		N/A
	Joints, raising/lowering devices		N/A
	Telescopic tubes etc.		N/A
	No twisting over 360°		P
5.10 (5.3.3)	Insulating bushings:		N/A
	- suitable fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- cables with protective sheath		N/A
5.10 (5.3.4)	Joints and junctions effectively insulated		N/A
5.10 (5.3.5)	Strain on internal wiring		N/A
5.10 (5.3.6)	Wire carriers		N/A
5.10 (5.3.7)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		P
5.10 (5.4)	Test to determine suitability of conductors having a reduced cross-sectional area		N/A
	Under test the temperature of the luminaire wiring	(see Annex 2)	N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	insulation not exceed the limits stated in Table 12.2		
	No damage to luminaire wiring after test		N/A

5.11 (8)	PROTECTION AGAINST ELECTRIC SHOCK		P
5.11 (8.2.1)	Live parts not accessible		P
	Basic insulated parts not used on the outer surface without appropriate protection		P
	Basic insulated parts not accessible with standard test finger on portable, settable and adjustable luminaires		P
	Basic insulated parts not accessible with Ø 50 mm probe from outside, other types of luminaires		N/A
	Lamp and starterholders in portable and adjustable luminaires comply with double or reinforced insulation requirements		N/A
	Basic insulation only accessible under lamp or starter replacement		N/A
	Protection in any position		P
	Double-ended tungsten filament lamp		N/A
	Insulation lacquer not reliable		N/A
	Double-ended high-pressure discharge lamp		N/A
	Relevant warning according to 3.2.18 fitted to the luminaire		N/A
5.11 (8.2.2)	Portable luminaire adjusted in most unfavourable position		N/A
5.11 (8.2.3.a)	Class II luminaire:		N/A
	- basic insulated metal parts not accessible during starter or lamp replacement		N/A
	- basic insulation not accessible other than during starter or lamp replacement		N/A
	- glass protective shields not used as supplementary insulation		N/A
5.11 (8.2.3.b)	BC lampholder of metal in class I luminaires shall be earthed		N/A
5.11 (8.2.3.c)	SELV circuits with exposed current carrying parts:		N/A
	Ordinary luminaire:		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	- voltage under load (V).....:		N/A
	- no-load voltage (V).....:		N/A
	- touch current if applicable (mA)		N/A
	One conductive part insulated if required		N/A
	Other than ordinary luminaire:		N/A
	- nominal voltage (V)		N/A
	Class III luminaire only for connection to SELV		P
	Class III luminaire not provided with means for protective earthing		N/A
5.11 (8.2.4)	Portable luminaire has protection independent of supporting surface		N/A
5.11 (8.2.5)	Compliance with the standard test finger or relevant probe		P
5.11 (8.2.6)	Covers reliably secured		P
5.11 (8.2.7)	Luminaire other than below with capacitor > 0,5 μ F not exceed 50 V 1 min after disconnection		P
	Portable luminaire with capacitor > 0,1 μ F (0.25) not exceed 34 V 1 s after disconnection		N/A
	Other luminaires with capacitor > 0,1 μ F (0.25) with plug and track adaptors not exceed 60 V 5 s after disconnection		N/A

5.12 (12)	ENDURANCE TEST AND THERMAL TEST		P
5.12.2 (-)	If IP > IP 20 relevant test of (12.4), (12.5) and (12.6) after (9.2) before (9.3) specified in 5.13		—
5.12 (12.2)	Selection of lamps and ballasts		—
	Lamp used according Annex B	(Lamp used see Annex 2)	—
	Controlgear if separate and not supplied	(Controlgear used see Annex 2)	—
5.12 (12.3)	Endurance test		P
	a) mounting- position	Normal mounting	—
	b) test temperature (°C).....:		—
	c) total duration (h)		—
	d) supply voltage (V).....:		—
	d) if not equipped with controlgear, constant		—

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	voltage/current (V) or (A)		
	e) luminaire ceases to operate		—
5.12 (12.3.2)	After endurance test:		P
	- no part unserviceable		P
	- luminaire not unsafe		P
	- no damage to track system		N/A
	- marking legible		P
	- no cracks, deformation etc.		P
5.12 (12.4)	Thermal test (normal operation)	(see Annex a/b/c)	P
5.12 (12.5)	Thermal test (abnormal operation)	(see Annex 2)	N/A
5.12 (12.6)	Thermal test (failed lamp control gear condition):		N/A
5.12 (12.6.1)	Through wiring or looping-in wiring loaded by a current of (A)		—
	- case of abnormal conditions.....		—
	- electronic lamp control gear		N/A
	- measured winding temperature (°C): at 1,1 Un		—
	- measured mounting surface temperature (°C) at 1,1 Un		N/A
	- calculated mounting surface temperature (°C)		N/A
	- track-mounted luminaires		N/A
5.12 (12.6.2)	Temperature sensing control		N/A
	- case of abnormal conditions.....		—
	- thermal link		N/A
	- manual reset cut-out		N/A
	- auto reset cut-out		N/A
	- measured mounting surface temperature (°C)		N/A
	- track-mounted luminaires		N/A
5.12 (12.7)	Thermal test (failed lamp control gear in plastic luminaires):		N/A
5.12 (12.7.1)	Luminaire without temperature sensing control		N/A
5.12 (12.7.1.1)	Luminaire with fluorescent lamp ≤ 70W		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	Test method 12.7.1.1 or Annex W		—
	Test according to 12.7.1.1:		N/A
	- case of abnormal conditions.....		—
	- Ballast failure at supply voltage (V)		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
	Test according to Annex W:		N/A
	- case of abnormal conditions.....		—
	- measured winding temperature (°C): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part (°C).....		—
	Ball-pressure test.....	See Test Table 5.15 (13.2.1)	N/A
5.12 (12.7.1.2)	Luminaire with discharge lamp, fluorescent lamp > 70W, transformer > 10 VA		N/A
	- case of abnormal conditions.....		—
	- measured winding temperature (°C): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part (°C).....		—
	Ball-pressure test.....	See Test Table 5.15 (13.2.1)	N/A
5.12 (12.7.1.3)	Luminaire with short circuit proof transformers ≤ 10 VA		N/A
	- case of abnormal conditions.....		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
5.12 (12.7.2)	Luminaire with temperature sensing control		N/A
	- thermal link.....	Yes ☐ No ☐	—
	- manual reset cut-out.....	Yes ☐ No ☐	—
	- auto reset cut-out.....	Yes ☐ No ☐	—
	- case of abnormal conditions.....		—

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	- highest measured temperature of fixing point/ exposed part (°C):..... :		—
	Ball-pressure test:..... :	See Test Table 5.15 (13.2.1)	N/A
5.12.1 (-)	Reduction 10 °C of measured temperatures if for outdoor use		—
5.12.2 (-)	Glass covers used within the thermal limits		N/A

5.13 (9)	RESISTANCE TO DUST AND MOISTURE		P
5.13.1 (-)	If IP > IP 20 the order of tests as specified in clause 5.12		P
5.13 (9.2)	Tests for ingress of dust, solid objects and moisture:		P
	- classification according to IP..... :	IP 66	—
	- mounting position during test..... :		—
	- fixing screws tightened; torque (Nm)..... :		—
	- tests according to clauses..... :		—
	- electric strength test afterwards		P
	a) no deposit in dust-proof luminaire		N/A
	b) no talcum in dust-tight luminaire		P
	c) no trace of water on current-carrying parts or on insulation where it could become a hazard		N/A
	c.1) For luminaires without drain holes – no water entry		P
	c.2) For luminaires with drain holes – no hazardous water entry		N/A
	d) no water in watertight or pressure watertight luminaire		P
	e) no contact with live parts (IP 2X)		N/A
	e) no entry into enclosure (IP 3X and IP 4X)		N/A
	e) no contact with live parts through drain holes and ventilation slots (IP3X and IP4X)		N/A
	f) no trace of water on part of lamp requiring protection from splashing water		P
	g) no damage of protective shield or glass envelope		P
5.13 (9.3)	Humidity test 48 h		P

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
5.14 (10)	INSULATION RESISTANCE AND ELECTRIC STRENGTH		P
5.14 (10.2.1)	Insulation resistance test		P
	Cable or cord covered by metal foil or replaced by a metal rod of mm Ø		—
	Insulation resistance (MΩ).....		—
	SELV		N/A
	- between current-carrying parts of different polarity:		N/A
	- between current-carrying parts and mounting surface.....		N/A
	- between current-carrying parts and metal parts of the luminaire.....		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts.....		N/A
	- Insulation bushings as described in Section 5		N/A
	Other than SELV		P
	- between live parts of different polarity.....		P
	- between live parts and mounting surface.....		P
	- between live parts and metal parts.....		P
	- between live parts of different polarity through action of a switch.....		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts.....		N/A
	- Insulation bushings as described in Section 5		N/A
5.14 (10.2.2)	Electric strength test		P
	Dummy lamp		N/A
	Luminaires with ignitors after 24 h test		N/A
	Luminaires with manual ignitors		N/A
	Test voltage (V).....		N/A
	SELV		P
	- between current-carrying parts of different polarity:	500 V	P
	- between current-carrying parts and mounting surface.....	500 V	P

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
	- between current-carrying parts and metal parts of the luminaire..... :	500 V	P
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :		N/A
	- Insulation bushings as described in Section 5 :		N/A
	Other than SELV		P
	- between live parts of different polarity..... :	1554 V	P
	- between live parts and mounting surface..... :	1554 V	P
	- between live parts and metal parts..... :	1554 V	P
	- between live parts of different polarity through action of a switch..... :		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :		N/A
	- Insulation bushings as described in Section 5 :		N/A
5.14 (10.3)	Touch current or protective conductor current (mA) :		P

5.15 (13)	RESISTANCE TO HEAT, FIRE AND TRACKING		N/A
5.15 (13.2.1)	Ball-pressure test..... :	See Test Table 5.15 (13.2.1)	P
5.15 (13.3.1)	Needle-flame test (10 s)..... :	See Test Table 5.15 (13.3.1)	P
5.15 (13.3.2)	Glow-wire test (650°C)..... :	See Test Table 5.15 (13.3.2)	P
5.15 (13.4)	Proof tracking test (IEC 60112)..... :	See Test Table 5.15 (13.4)	N/A

5.7 (11.2)	TABLE I: Creepage distances and clearances	P
	Minimum distances (mm) for a.c. up to 30 kHz sinusoidal voltages	P

IEC 60598-2-5							
Clause	Requirement + Test				Result - Remark		Verdict
	Applicable part of IEC 60598-1 Table 11.1.A*, 11.1.B* and 11.2*						P
	Insulation type **	Measured clearance	Required		Measured creepage	Required	
			clearance	*Table		creepage	*Table
Distance 1:	B	> 1.5	1.5	11.1B	> 2.8	2.8	11.1A
Working voltage (V)..... :					277 V		—
PTI..... :					< 600 ☒ ≥ 600 ☐		—
Pulse voltage or U_P if applicable (kV)					-		—
Supplementary information: Between L and N before fuse							
Distance 2:	B	> 1.5	1.5	11.1B	> 2.8	2.8	11.1A
Working voltage (V)..... :					277 V		—
PTI..... :					< 600 ☒ ≥ 600 ☐		—
Pulse voltage or U_P if applicable (kV)					-		—
Supplementary information: Between live parts and metal enclosure							
Distance 3:	B	> 1.5	1.5	11.1B	> 2.8	2.8	11.1A
Working voltage (V)..... :					277 V		—
PTI..... :					< 600 ☒ ≥ 600 ☐		—
Pulse voltage or U_P if applicable (kV)					-		—
Supplementary information: Between live parts and mounting surface							

** Insulation type: B – Basic; S – Supplementary; R – Reinforced. See also IEC 60598-1 Annex M.

5.7 (11.2)	TABLE II: Creepage distances and clearances						N/A
Minimum distances (mm) for a.c. higher than 30 kHz sinusoidal voltages							
Applicable part of IEC 61347-1 Table 7 and 8* or IEC 60664-4 Table 1 and 2							
Distances	Insulation type **	Measured clearance	Required		Measured creepage	Required	
			clearance	*Table		creepage	*Table
Distance 1:							
Working voltage (V)..... :							—
Frequency if applicable (kHz)..... :							—
PTI..... :					< 600 ☐ ≥ 600 ☐		—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV) :							—

IEC 60598-2-5							
Clause	Requirement + Test				Result - Remark		Verdict
Supplementary information:							
Distance 2:							
Working voltage (V)..... :							—
Frequency if applicable (kHz)..... :							—
PTI..... :					< 600 ☐ ≥ 600 ☐		—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV)							—
Supplementary information:							
Distance 3:							
Working voltage (V)..... :							—
Frequency if applicable (kHz)..... :							—
PTI..... :					< 600 ☐ ≥ 600 ☐		—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV)							—
Supplementary information:							

** Insulation type: B – Basic; S – Supplementary; R – Reinforced.

5.15 (13.2.1)	TABLE: Ball Pressure Test of Thermoplastics			P
Allowed impression diameter (mm):		2		—
Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)	
LED lens	See Annex 1	125°C	0.7	
LED PCB	See Annex 1	125°C	0.4	
Supplementary information: -				

5.15 (13.3.1)	TABLE: Needle-flame test (IEC 60695-11-5)					P
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict	
LED PCB	See Annex 1	10	No	0	pass	

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict

Supplementary information: -

5.15 (13.3.2)	TABLE: Glow-wire test (IEC 60695-2-11)				N/A
Glow wire temperature :			650°C		—
Object/ Part No./ Material	Manufacturer/ trademark		Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
LED lens	See Annex 1		No	0	pass
Supplementary information: -					

5.15 (13.4)	TABLE: Proof tracking test (IEC 60112)				N/A
Test voltage PTI :		175 V			—
Object/ Part No./ Material	Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens			Verdict
Supplementary information:					

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 1	TABLE: Critical components information					P
Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity 1)
Supply cord (3 cores)	B	Queshan Yuqiang Cable Co., Ltd.	H07RN-F	450/750V, 105°C, 1,5mm ²	EN 50525-2-21	VDE 40044073*
Alt	B	GUANG DONG RIFENG ELECTRICAL CABLE CO LTD	H07RN-F	450/750V, 105°C, 1,5mm ²	EN 50525-2-21	VDE 40015999*
Alt	B	Dongguan Wandu Cable Co., Ltd	H07RN-F	450/750V, 105°C, 1,5mm ²	EN 50525-2-21	VDE 40052148*
Alt	B	SHENZHEN XINSUN ELECTRIC CO LTD	H07RN-F	450/750V, 105°C, 1,5mm ²	EN 50525-2-21	VDE 40056890*
Alt	B	NISSEI ELECTRIC(SHENZHEN) CO.,LTD.	H07RN-F	450/750V, 105°C, 1,5mm ²	EN 50525-2-21	VDE 40055357*
Alt	B	Dong Guan Recheer Electric Wire & Cable Co., Ltd.	H07RN-F	450/750V, 105°C, 1,5mm ²	EN 50525-2-21	VDE 40015173*
Dimming cord	B	GUANG DONG RIFENG ELECTRICAL CABLE CO LTD	H05RN-F	300/500V, 105°C, 2x1,0mm ² or 2x0.75mm ² or 2x0.5mm ²	EN 50525-2-21	VDE 40015999*
Alt	D	Dongguan Wandu Cable Co., Ltd	H05RN-F	300/500V, 105°C, 2x1,0mm ² or 2x0.75mm ² or 2x0.5mm ²	EN 50525-2-21	VDE 40052148*
Alt	D	SHENZHEN XINSUN ELECTRIC CO LTD	H05RN-F	300/500V, 105°C, 2x1,0mm ² or 2x0.75mm ² or 2x0.5mm ²	EN 50525-2-21	VDE 40056890*
Alt	D	NISSEI ELECTRIC(SHENZHEN) CO.,LTD.	H05RN-F	300/500V, 105°C, 2x1,0mm ² or 2x0.75mm ² or 2x0.5mm ²	EN 50525-2-21	VDE 40055357*
Alt	D	Dong Guan Recheer Electric Wire & Cable Co., Ltd.	H05RN-F	300/500V, 105°C, 2x1,0mm ² or 2x0.75mm ² or 2x0.5mm ²	EN 50525-2-21	VDE 40015173*
Alt.	D	LINOYAELECTRONIC TECHNOLOGY COLTD	21996	300/500V, 105°C, 2x 22AWG or 2x 20AWG or 2x 18AWG	UL 758 +IEC/EN 61347-1; IEC/EN 61347-2-13	ULE 315619* +Tested withappliance#
Alt.	D	SHENZHEN CHAOJIE ELECTRONICS COLTD	2517	300/500V, 105°C, 2x 22AWG or 2x 20AWG or	UL 758 +IEC/EN 61347-1; IEC/EN	ULE484929* +Tested withappliance#

Tel: (86)755-85277785

Fax: (86)755-23705230

E-mail: postmaster@aoc-cert.comWebsite: <http://www.aoc-cert.com>

TRF No. IEC60598_2_5F

IEC 60598-2-5						
Clause	Requirement + Test			Result - Remark		Verdict
				2x 18AWG	61347-2-13	
Earthing wire	B	Shenzhen Jinhongyu Electricity Industry Technology Co Ltd	1015	600V; 105°C; 18/16/14/12AWG	UL 758 IEC/EN IEC 60598-1 IEC/EN 60598-2-5	UL E485746*+ Test with appliance#
Alt.	B	SHENZHEN XINSUN ELECTRIC CO LTD	1015	600V; 105°C; 18/16/14/12AWG	UL 758 IEC/EN IEC 60598-1 IEC/EN 60598-2-5	UL E365619*+ Test with appliance#
Alt.	B	Xin Sheng Terminal Mfg Ltd	1015	600V; 105°C; 18/16/14/12AWG	UL 758 IEC/EN IEC 60598-1 IEC/EN 60598-2-5	UL E328303*+ Test with appliance#
Alt.	B	NISSEIELECTRIC(SHENZHEN)CO.,LTD.	1015	600V; 105°C; 18/16/14/12AWG	UL 758 IEC/EN IEC 60598-1 IEC/EN 60598-2-5	UL E318424*+ Test with appliance#
Alt.	B	DONGGUAN CHENG XING ELECTRONIC CO LTD	1015	18AWG; 105°C; 600V	UL 758 IEC/EN 60598-1 IEC/EN 60598-2-5	UL E249743* + Tested with appliance#
Alt.	D	Interchangeable	1015	600V; 105°C; 18/16/14/12AWG	UL 758	UL
Terminal block (supply)	B	Jiang Men Krealux Electrical Appliances Co. Ltd.	T10	750V, 6.0mm ²	EN 60998-1; EN 60998-2-1	VDE 40018381
Insulation sheet	B	SICHUAN DONGFANG INSULATING MATERIAL CO LTD	DFR3A(d); DFR3713 A(d)	PP; V-0; 110°C	UL 94; IEC/EN 60598-1; IEC/EN 60598-2-5	UL E199019 Test with appliance
SPD protector	B	Guangdong ZP Lightning Protection Technology Co., Ltd.	ZP-LSP10-S/T	AC320V; 50/60Hz; 85°C; I _{in} =5KA; U _{oc} =10KV; U _p =1,2KV	EN 61643-11	TUV R 50405142
			ZP-LSP10-S	320VAC; 50/60Hz; 85°C; I _{in} =5KA; U _{oc} =10KV; type 2 or type 3		
			ZP-LSP20-S	320VAC; 50/60Hz; 85°C; I _{in} =10KA; U _{oc} =20KV		

IEC 60598-2-5						
Clause	Requirement + Test			Result - Remark		Verdict
Alt.	D	Shenzhen Zpwy Technology Co., Ltd.	ZP-LED-P10D ZP-LED-T10D ZP-LED-S10D	320VAC; 50/60Hz; 85°C; in=5KA; Uoc=10KV; type 2 or type 3 IP67	EN 61643-11	TÜVRheinland Mark R 50516300 0001
Alt.	D	Shenzhen Zpwy Technology Co., Ltd.	ZP-LSP10-PR	320VAC; 50/60Hz; 85°C; in=5KA; Uoc=10KV; type 2 or type 3 IP67	EN 61643-11	TÜVRheinland Mark R 50538341 0001
Alt.	D	Shenzhen Zpwy Technology Co., Ltd.	ZP-LSP20-PY	320VAC; 50/60Hz; 85°C; in=5KA; Uoc=20KV; type 2 or type 3 IP67	EN 61643-11	TÜVRheinland Mark R 50538341 0001
Alt.	D	SHENZHEN RUILONGYUAN ELECTRONICS Co.,Ltd	TP20D-277	AC 277V; 50/60Hz; 85°C; In:10KA; Uoc:20KV; Up:2.0Kv (L~N/PE) Up:2.5Kv (N~PE)	EN 61643-11	TUV R 50427906
Alt.	D	SHENZHEN RUILONGYUAN ELECTRONICS Co.,Ltd	TP10E TP10B TP10C TP10S	AC 320V; 50/60Hz; 85°C; In:5KA; Uoc:10KV;	EN 61643-11	TUV Rheinland AN 50569398 0001
Alt.	D	SHENZHEN RUILONGYUAN ELECTRONICS Co.,Ltd	TP10D TP10R	AC 277V; 50/60Hz; 85°C; In:5KA; Uoc:10KV; Up:1.5Kv (L~N/PE) Up:1.8Kv (N~PE)	EN 61643-11	TUV R 50427906 0005
Alt.	D	ShenzhenZhongyuanTechnology Co.,Ltd.	ZYS S10WLED	Uc: 350VAC; 40°Cto 85°C	EN 61643-11	TÜVRheinland R50477550
Alt.	D	Linoya Electronic Technology Co., Ltd	LYSPD20D	300VAC; 50/60Hz; 80°C; in=10KA; Uc=320V; type 3	EN 61643-11	TUV Rheinland R 50463812 001
			LYSPD10D	300VAC; 50/60Hz; 80°C; in=5KA; Uc=320V; type 3		
			LYSPD10D 480	500VAC; 50/60Hz; 80°C; in=10KA; type 3		
			LYSPD20D 480	500VAC; 50/60Hz; 80°C; in=20KA; type 3		
Alt.	B	Xiamen SET Electronics Co.,Ltd.	SD10C277LM	320VAC; 85°C	IEC/EN 61643-11	DEKRA CB NL-41005

IEC 60598-2-5						
Clause	Requirement + Test			Result - Remark		Verdict
Alt.	B	Xiamen SET Electronics Co.,Ltd.	SD10C27 7AHT	320VAC; 85°C	IEC/EN 61643-11	DEKRA AOC 3183404.05
Terminal block ((input, output and dimmer))	B	WAGO Kontakttechnik GmbH & Co. KG	224 series	600V; 2,5mm ²	IEC/EN61643- 11	TUV R 50405142
Terminal block (input, output and dimmer) Input:Excluding ESM series drivers Output:Excluding EUCCO, S6, HDE series drivers	B	WAGO KONTAKTTECHNIK GMBH & CO KG	221 series	450V;0.2-4mm ² ; 85°C;32A	IEC/EN 60598-1 IEC/EN 60598-2- 2	DEKRA ENEC: 71-101731*
Alt.	B	WAGO INNOVATIVE CONNECTIONS	222 series	400V;2.5-4mm ² ; 32A	IEC/EN 60598-1 IEC/EN 60598-2- 2	UL ENEC- 01360*
Alt.	B	Jiangxi Gaochao industrial co., ltd	GC222-5 GC222-3 GC222-2	450V; 0,2-4mm ² ; 110°C	IEC/EN 60998-1 IEC/EN 60998-2-2	TÜV SÜD B 003006 0008*
Alt.	B	Viola Direkt GmbH	UC02M UC03M UC05M	450V; 0,2-2.5mm ² ;	DIN EN 60998-1 DIN EN 60998-2-2	VDE 40051254
Alt.	B	Yuyao Sineyi Electronic Technology Co., Ltd.	P02	450V; 0,5-4mm ² ; 110°C; 16A	IEC/EN 60998-1 IEC/EN 60998-2-2	TÜVRheinla nd R 50420331*

IEC 60598-2-5						
Clause	Requirement + Test			Result - Remark		Verdict
Output cord of LED driver(2 or 3 or 4 or 5 cores used with above 3 pin or 4 pin or 5 pin connector) (LED driver box separated mounting with luminaire) 3 cores for S6 600D/R36 0 4 cores for S6 1K2D/R50 0 or HDE 1800STH5 00C 5 cores for S6 1K8D/R50 0 or HDE 1800STH5 00C	B	GUANG DONG RIFENG ELECTRICAL CABLE CO LTD	H05RN-F	300/500V, 105°C 1,0mm ² or 1,5mm ²	EN 50525-2-21	VDE 40015999
			H07RN-F	450/750V, 105°C 1,0mm ² or 1,5mm ²		
Alt.	D	Dongguan Wandu Cable Co., Ltd	H05RN-F	300/500V, 105°C 1,0mm ² or 1,5mm ²	EN 50525-2-21	VDE 40052148
			H07RN-F	450/750V, 105°C 1,0mm ² or 1,5mm ²		
Alt.	D	SHENZHEN XINSUN ELECTRIC CO LTD	H05RN-F	300/500V, 105°C 1,0mm ² or 1,5mm ²	EN 50525-2-21	VDE 40056890
			H07RN-F	450/750V, 105°C 1,0mm ² or 1,5mm ²		
Alt.	D	NISSEI ELECTRIC(SHENZHEN) CO.,LTD.	H05RN-F	300/500V, 105°C 1,0mm ² or 1,5mm ²	EN 50525-2-21	VDE 40055357
			H07RN-F	450/750V, 105°C 1,0mm ² or 1,5mm ²		
Alt.	D	Dong Guan Recheer Electric Wire & Cable	H05RN-F	300/500V, 105°C 1,0mm ² or 1,5mm ²	EN 50525-2-	VDE

IEC 60598-2-5						
Clause	Requirement + Test			Result - Remark		Verdict
		Co., Ltd.	H07RN-F	450/750V, 105°C 1,0mm ² or 1,5mm ²	21	40015173
Input cord of LED module(2 or 3 cores)	B	GUANG DONG RIFENG ELECTRICAL CABLE CO LTD	H05RN-F	300/500V, 105°C 1,0mm ² or 1,5mm ²	EN 50525-2-21	VDE 40015999
			H07RN-F	450/750V, 105°C 1,0mm ² or 1,5mm ²		
Alt.	D	Dongguan Wandu Cable Co., Ltd	H05RN-F	300/500V, 105°C 1,0mm ² or 1,5mm ²	EN 50525-2-21	VDE 40052148
			H07RN-F	450/750V, 105°C 1,0mm ² or 1,5mm ²		
Alt.	D	SHENZHEN XINSUN ELECTRIC CO LTD	H05RN-F	300/500V, 105°C 1,0mm ² or 1,5mm ²	EN 50525-2-21	VDE 40056890
			H07RN-F	450/750V, 105°C 1,0mm ² or 1,5mm ²		
Alt.	D	NISSEI ELECTRIC(SHENZHEN) CO.,LTD.	H05RN-F	300/500V, 105°C 1,0mm ² or 1,5mm ²	EN 50525-2-21	VDE 40055357
			H07RN-F	450/750V, 105°C 1,0mm ² or 1,5mm ²		
Alt.	D	Dong Guan Recheer Electric Wire & Cable Co., Ltd.	H05RN-F	300/500V, 105°C 1,0mm ² or 1,5mm ²	EN 50525-2-21	VDE 40015173
			H07RN-F	450/750V, 105°C 1,0mm ² or 1,5mm ²		
LED lens	C	LG CHEM (GUANGZHOU) ENGINEERING PLASTICS CO LTD	LUPOY GP1006F(m)(f1), LUPOY GP1006F(f1)	V-0, 110°C	EN 60598-1 EN 60598-2-5	UL E248280 Test with appliance
Alt.	D	TEIJIN POLYCARBONATE SINGAPORE PTE LTD	L-1250U(#)(f1) L-1250V(#)(f1) L-1250Z(#)(f1)	V-2; 130°C	EN 60598-1 EN 60598-2-5	UL E245526*+ Test with appliance
Alt.	D	IDEMITSU KONSAN CO LTD	LEV2200KL	V-2; 130°C	IEC/EN 60598-1 IEC/EN 60598-2-5	UL E48268*+ Test with appliance
Alt.	D	TEIJIN LIMITED RESIN AND PLASTIC	G-35(mm)(r1)	HB; 130°C	IEC/EN 60598-1 IEC/EN 60598-2-5	UL E50075*+ Tested with appliance#

IEC 60598-2-5						
Clause	Requirement + Test			Result - Remark		Verdict
LED PCB	B	SHENZHEN ZYD ELECTRONIC TECHNOLOGY CO LTD	ZYD-L	V-0; 130°C	UL 94 IEC/EN 60598-1 IEC/EN 60598-2- 5	UL E483786 Test with appliance
Alt.	B	SHENZHEN MINGYU CIRCUIT CO LTD	MY-L;MY-L1 (ASP1)	V-0; 130°C	UL 94 IEC/EN 60598-1 IEC/EN 60598-2- 5	UL E503093*+ Tested with appliance
Alt.	B	HUIZHOU SEA INDUSTRY LTD	HC-02	V-0; 130°C	UL 94 IEC/EN 60598-1 IEC/EN 60598-2- 5	UL E346036*+ Tested with appliance
Alt.	B	SHENZHEN HUAYU CIRCUITS CO LTD	HY-MH(ASP 1)	V-0; 130°C	UL 94 IEC/EN 60598-1 IEC/EN 60598-2- 5	UL E465882*+ Tested with appliance
Alt.	B	Hunan Cheng Chuang Xin Technology Co Ltd	CCX-03	V-0; 130°C	UL 94 IEC/EN 60598-1 IEC/EN 60598-2- 5	UL E502083*+ Tested with appliance
Alt.	B	SHENZHEN XINLONGYE ELECTRONIC TECHNOLOGY CO LTD	XLY-01	V-0; 130°C	UL 94 IEC/EN 60598-1 IEC/EN 60598-2- 5	UL E496651*+ Tested with appliance
Alt.	D	Interchangeable	-	V-0; 130°C	UL 94 IEC/EN 60598-1 IEC/EN 60598-2- 5	UL
LED (353 5)	B	SAMSUNG	LH351B	If=1500mA max; Vf=2,86-3,12V; 2700-6500K	EC TR 62778; IEC 62031; IEC 62471	Tested with appliance#
LED (353 5)	B	SAMSUNG	LH351C	If=2000mA max; Vf=2, 6-3,1V; 2700-6500K	EC TR 62778; IEC 62031; IEC 62471	Tested with appliance#
LED (353 5)	B	Bridgelux	BXEX 3535	If=1800mA max; Vf=2, 7-3,1V; 2700-6500K	EC TR 62778; IEC	Tested with appliance#

IEC 60598-2-5						
Clause	Requirement + Test			Result - Remark		Verdict
					62031; IEC 62471	
LED (2424)	B	Bridgelux	BXCP 2424	If=1400mA max; Vf=2, 8-3,3V; 1800-6500K	EC TR 62778; IEC 62031; IEC 62471	Tested with appliance#
LED (2424)	B	OSRAM	GW PLLRA1.P M	If=1500mA max; Vf=2, 7-3,2V; 2200-6500K	EC TR 62778; IEC 62031; IEC 62471	Tested with appliance#
LED (3030)	B	luimuleds	LUXEON 3030 2D	If=240mA; Vf=5.8-6.6V; 2700-6500K	IEC TR 62778; IEC 62031; IEC 62471	Tested with appliance#
LED (3535)	B	luimuleds	SST-20F-WAL	If=1500mA max; Vf=2,5-3,1V; 2700-6500K	IEC TR 62778; IEC 62031; IEC 62471	Tested with appliance#
LED (2835)	B	luimuleds	L 1 2 8 – A AB B R C 3 5 00 D D D	If=120mA max; Vf=8,6-9,6V; 2700-6500K	IEC TR 62778	Tested with appliance#
DC waterproof connector (3 pin)	B	Shenzhen Lilutong Electronic Technology Co., Ltd	LLT-M19-25003F3; LLT-M19-25003M3	600VAC; 25A; 2.5mm ² ; 105°C; IP67	EN 61984	TÜV SÜD: No. B 090230 0010*
DC waterproof connector (4 pin)	B	Shenzhen Lilutong Electronic Technology Co., Ltd	LLT-M19-25004F3; LLT-M19-25004M3	600VAC; 25A; 2.5mm ² ; 105°C; IP67	EN 61984	TÜV SÜD: No. B 090230 0010*
DC waterproof connector (5 pin)	B	Shenzhen Lilutong Electronic Technology Co., Ltd	LLT-M19-25005F3; LLT-M19-25005M3	600VAC; 25A; 2.5mm ² ; 105°C; IP67	EN 61984	TÜV SÜD: No. B 090230 0010*
DC waterproof connector (3 pin)	B	Shenzhen Lilutong Electronic Technology Co., Ltd	LLT-M25-30003F3; LLT-M25-30003M3	600VAC; 30A; 4.0mm ² ; 105°C; IP67	EN 61984	TÜV SÜD: No. B 090230 0010*

IEC 60598-2-5						
Clause	Requirement + Test			Result - Remark		Verdict
DC waterproof connector (4 pin)	B	Shenzhen Lilutong Electronic Technology Co., Ltd	LLT-M25-30004F3; LLT-M25-30004M3	600VAC; 30A; 4.0mm ² ; 105°C; IP67	EN 61984	TÜV SÜD: No. B 090230 0010*
DC waterproof connector (5 pin)	B	Shenzhen Lilutong Electronic Technology Co., Ltd	LLT-M25-30005F3; LLT-M25-30005M3	600VAC; 30A; 4.0mm ² ; 105°C; IP67	EN 61984	TÜV SÜD: No. B 090230 0010*
LED driver	B	INVENTRONICS (HANGZHOU) INC	EUM-480S280 MG-xxxx EUM-480S280B G-xxxx	Input: 100- 277VAC, 50/60Hz, Max.5,0A ; Output: 86- 228Vdc, Max.2,8A, Max.480W; ta50°C; tc90°C; IP67; Uout: 280Vdc, Independent	IEC/EN 61347- 1 IEC/EN 61347-2-13 IEC/EN 62384	TUV SUD No. U6 07913603 98*
LED driver	B	INVENTRONICS (HANGZHOU) INC	EUM-600S350 MG-xxxx EUM-600S350B G-xxxx	Input: 100- 277VAC, 50/60Hz, Max.6,9A ; Output: 97,1- 262Vdc, Max.3,5A, Max.680W; ta50°C; tc90°C; IP67; Uout: 300Vdc, Independent	IEC/EN 61347- 1 IEC/EN 61347-2-13 IEC/EN 62384	TUV SUD ENEC25 No. U6 07913603 25*
LED driver	B	INVENTRONICS (HANGZHOU) INC	EUM-880S420 MG-xxxx	Input: 100- 277VAC, 50/60Hz, Max.7,6A ; Output: 104- 294Vdc, Max.4,2A, Max.880W; 100-200 ta45°C; 200-277v~ta55°C ;tc90°C; IP67; Uout: 350Vdc, Independent	IEC/EN 61347- 1 IEC/EN 61347-2-13 IEC/EN 62384	TUV SUD ENEC25 No. U6 07913603 46*
LED driver	B	DELTA ELECTRONICS (WUHU) LTD.	EUCO-1K5140GL A EUCO-1K5140G DA	Input: 220- 400VAC, 50/60Hz, 7,8- 4,5A, 1596W(Max.); Output: 260- 500Vdc, 0,5- 1,4A, Max.500W(1 channel)(3 Independent channels, total: 1500W); ta 50°C; tc 85°C; IP66; Uout: 600Vdc(Max.), Independent	IEC/EN 61347- 1 IEC/EN 61347-2-13 IEC/EN 62384	TUV Rh DE 2-027713-M1 TUV Rh ENEC 18: HN 69290102 0001-0006

IEC 60598-2-5						
Clause	Requirement + Test			Result - Remark		Verdict
LED driver	B	Powerland Technology Inc.	600FGH420C-xxxxx	Input: 100-277VAC,50/60Hz,Max.3,3A,Max.660W;Output: 150-420Vdc, 0,8-2,5A ,Max.240W; Uout:310Vdc; tc90°C; IP65; CC;Independent;Class I; Isolating.	IEC/EN 61347- 1 IEC/EN 61347-2-13 IEC/EN 62384	TUV SUD U6 125095 0016*
LED driver	B	Shen Zhen MOSO Electronics Technology Co.,Ltd.	N7-240M260A12	Input: 100-277VAC,50/60Hz,Max.2,8A,Max.280W;Output: 180-260Vdc, 0,11-1,11A ,Max.240W; Uout:310Vdc; ta50°C;tc90°C; IP67; CC;Independent;Class I; Isolating.	IEC/EN 61347- 1 IEC/EN 61347-2-13 IEC/EN 62493	TUV SUD N8A 077716 0314*
LED driver	B	Shen Zhen MOSO Electronics Technology Co.,Ltd.	S6-600D360 S6-600R360	Input: 220-415VAC,50/60Hz,Max.3,2A,Max.660W;Output: 172-360Vdc, 0.3-3A ,Max.600W; Uout:420Vdc; ta50°C;tc90°C; IP66; CC;Independent;Class I; Isolating.	IEC/EN 61347- 1 IEC/EN 61347-2-13 IEC/EN 62384	TUV Rh ENEC 18: HN69290675 0001
LED driver	B	Shen Zhen MOSO Electronics Technology Co.,Ltd.	S6-1K2D500 S6-1K2R500	Input: 220-400VAC,50/60Hz,Max.6,0A,Max.1300W;Output: 260-500Vdc, 0.18-1.8A, Max.600Wx 2; Uout: 600Vdc; ta50°C;tc90°C; IP66; CC;Independent;Class I; Nonisolating.	IEC/EN 61347- 1 IEC/EN 61347-2-13 IEC/EN 62384	TUV Rh ENEC 18: HN 69290750*
LED driver	B	Shen Zhen MOSO Electronics Technology Co.,Ltd.	S6-1K8D500 S6-1K8R500	Input: 220-400VAC,50/60Hz,Max.9,0A,Max.1900W;Output: 260-500Vdc, 0.18-1.8A, Max.600Wx 3; Uout:600Vdc; ta50°C;tc90°C; IP66; CC;Independent; Class I; Nonisolating.	IEC/EN 61347- 1 IEC/EN 61347-2-13 IEC/EN 62384	TUV Rh ENEC 18: HN 69290750*
LED driver	B	Shenzhen Huadian Lighting Co.,Ltd.	HDE-1800STH500C	Input: 200-480VAC,50/60Hz,Max.9,6A;Output: 280-500Vdc, (1.2-2.15)A x 3, 600Wx 3; Uout:550Vdc;	IEC/EN 61347- 1 IEC/EN 61347-2-	TUV SUD ENEC 25: U6 1045820011*

IEC 60598-2-5						
Clause	Requirement + Test			Result - Remark		Verdict
				ta50°C;tc90°C; IP66; CC;Independent; Class I; Autowound.	13 IEC/EN 62384	
LED driver	B	Powerland Technology Inc.	1800STH500 C-xxxxx	Input: 200-480VAC,50/60Hz,Max.9,8A;Output: 270-490Vdc,(0,6-2,2)A x 3, 600Wx 3; Uout:550Vdc; ta50°C;tc90°C; IP66; CC;Independent; Class I	IEC/EN 61347-1 IEC/EN 61347-2-13 IEC/EN 62384	TUV SUD ENEC 25: U6 1250950011*
Supplementary information: 1) Provided evidence ensures the agreed level of compliance. See OD-CB2039. * License available upon request. # Please refer summary of testing in TRF for the test standard publication year. The codes above have the following meaning: A - The component is replaceable with another one, also certified, with equivalent characteristics B - The component is replaceable if authorised by the test house C - Integrated component tested together with the appliance D - Alternative component						

ANNEX 2	TABLE: Thermal tests of Section 12		P
	Type reference.....:	VL-FL-G4.5-1800W	—

IEC 60598-2-5							
Clause	Requirement + Test				Result - Remark		Verdict
	Lamp used.....:				LEDs		—
	Lamp control gear used.....:				LED controlgear		—
	Mounting position of luminaire.....:				Normal mounting		—
	Supply wattage (W).....:				1800 W		—
	Supply current (A).....:				-		—
	Temperatures in test 1 - 4 below are corrected for ta (°C)				50 °C		—
	- abnormal operating mode.....:				-		—
1.12 (12.4)	- test 1: rated voltage				-		—
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current				1.06×240 V		—
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage.....:				-		—
	Through wiring or looping-in wiring loaded by a current of A during the test				-		—
1.12 (12.5)	- test 4: 1,1 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current.....:				-		—
Temperature measurements (°C)							
Part	Ambient	Cl. 12.4 – normal				Cl. 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
Supply cord	50	-	51.3	-	90	-	-
Driver tc	50	-	65.5	-	90	-	-
Metal enclosure	50	-	59.8	-	90	-	-
LED PCB	50	-	81.8	-	130	-	-
LED cover	50	-	70.4	-	cl.13.1	-	-
Wire near LED PCB	50	-	72.6	-	90	-	-
Mounting surface	50	-	59.8	-	90	-	-
Supplementary information :-							

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
ANNEX 3	Screw terminals (part of the luminaire)		N/A
(14)	SCREW TERMINALS		N/A
(14.2)	Type of terminal.....:		—
	Rated current (A).....:		—
(14.3.2.1)	One or more conductors		N/A
(14.3.2.2)	Special preparation		N/A
(14.3.2.3)	Terminal size		N/A
	Cross-sectional area (mm ²).....:		—
(14.3.3)	Conductor space (mm).....:		N/A
(14.4)	Mechanical tests		N/A
(14.4.1)	Minimum distance		N/A
(14.4.2)	Cannot slip out		N/A
(14.4.3)	Special preparation		N/A
(14.4.4)	Nominal diameter of thread (metric ISO thread).....:	M	N/A
	External wiring		N/A
	No soft metal		N/A
(14.4.5)	Corrosion		N/A
(14.4.6)	Nominal diameter of thread (mm).....:		N/A
	Torque (Nm).....:		N/A
(14.4.7)	Between metal surfaces		N/A
	Lug terminal		N/A
	Mantle terminal		N/A
	Pull test; pull (N).....:		N/A
(14.4.8)	Without undue damage		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
ANNEX 4	Screwless terminals (part of the luminaire)		N/A
(15)	SCREWLESS TERMINALS		N/A
(15.2)	Type of terminal.....:		—
	Rated current (A).....:		—
(15.3.1)	Material		N/A
(15.3.2)	Clamping		N/A
(15.3.3)	Stop		N/A
(15.3.4)	Unprepared conductors		N/A
(15.3.5)	Pressure on insulating material		N/A
(15.3.6)	Clear connection method		N/A
(15.3.7)	Clamping independently		N/A
(15.3.8)	Fixed in position		N/A
(15.3.10)	Conductor size		N/A
	Type of conductor		N/A
(15.5)	Terminals and connections for internal wiring		N/A
(15.5.1)	Mechanical tests		N/A
(15.5.1.1.1)	Pull test spring-type terminals (4 N, 4 samples).....:		N/A
(15.5.1.1.2)	Pull test pin or tab terminals (4 N, 4 samples).....:		N/A
	Insertion force not exceeding 50 N		N/A
(15.5.1.2)	Permanent connections: pull-off test (20 N)		N/A
(15.5.2)	Electrical tests		N/A
	Voltage drop (mV) after 1 h (4 samples).....:		N/A
	Voltage drop of two inseparable joints		N/A
	Number of cycles:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples).....:		N/A
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples).....:		N/A
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples).....:		N/A
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples).....:		N/A
(15.6)	Terminals and connections for external wiring		N/A

IEC 60598-2-5			
Clause	Requirement + Test	Result - Remark	Verdict
(15.6.1)	Conductors		N/A
	Terminal size and rating		N/A
15.6.2	Mechanical tests		N/A
(15.6.2.1)	Pull test spring-type terminals or welded connections (4 samples); pull (N)		N/A
(15.6.2.2)	Pull test pin or tab terminals (4 samples); pull (N)		N/A
(15.6.3)	Electrical tests		N/A
	Tests according 15.6.3.1 + 15.6.3.2 in IEC 60598-1		N/A

(15.6.3.1) (15.6.3.2)	TABLE: Contact resistance test / Heating tests										N/A
	Voltage drop (mV) after 1 h										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop of two inseparable joints										
	Voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV) :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop after 50th alt. 100th cycle										
	Max. allowed voltage drop (mV) :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV) :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 50th alt. 100th cycle										

IEC 60598-2-5										
Clause	Requirement + Test					Result - Remark				Verdict
	Max. allowed voltage drop (mV) :									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										
Supplementary information:										

ANNEX 5	EN 62493		
Assessment of lighting equipment related to human exposure to electromagnetic fields EMF			
	The tested product also complies to the requirements of EN 62493: 2015		--
	Limit.....0.85	Measured max.....0.012 %	P

Attachment No.1**EU_GD_IEC60598_2_5E ATTACHMENT**

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

ATTACHMENT TO TEST REPORT IEC 60598-2-5 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES LUMINAIRES PART 2: PARTICULAR REQUIREMENTS SECTION 5: FLOODLIGHTS			
Differences according to: EN 60598-2-5:2015 used in conjunction with EN 60598-1:2015			
Annex Form No: EU_GD_IEC60598_2_5E			
Annex Form Originator: IMQ S.p.A.			
Master Annex Form: 2016-08			
Copyright © 2016 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			

	CENELEC COMMON MODIFICATIONS (EN)	P
--	--	----------

5.5 (3)	MARKING	P
5.5 (3.3.101)	For luminaires not supplied with terminal block: Adequate warning on the package	P

5.6 (4)	CONSTRUCTION	P
5.6 (4.11.6)	Electro-mechanical contact systems	P

5.10 (5)	EXTERNAL AND INTERNAL WIRING	P
5.10 (5.2.1)	Connecting leads	P
	- without a means for connection to the supply	N/A
	- terminal block specified	P
	- relevant information provided	P
	- compliance with 4.6, 4.7.1, 4.7.2, 4.10.1, 11.2, 12 and 13.2 of Part 1	P
5.10 (5.2.2)	Cables equal to EN 50525	P
	Replace table 5.1 – Supply cord	P

5.12 (12)	ENDURANCE TESTS AND THERMAL TESTS	P
5.12	Thermal test (normal operation)	P

Attachment No.1**EU_GD_IEC60598_2_5E ATTACHMENT**

Clause	Requirement + Test	Result - Remark	Verdict
(12.4.2c)	see footnote c to table 12.2 relating to unsleeved fixed wiring		

ZB	ANNEX ZB, SPECIAL NATIONAL CONDITIONS (EN)		N/A
(3.3)	DK: power supply cords of class I luminaires with label		N/A
(4.5.1)	DK: socket-outlets		N/A
(5.2.1)	CY, DK, FI, GB: type of plug		N/A

ZC	ANNEX ZC, NATIONAL DEVIATIONS (EN)		N/A
(4 & 5)	FR: Shuttered socket-outlets 10/16A		N/A
	FR: Safety requirements for high buildings (Arrêté du 30 décembre 2011 portant règlement de sécurité pour la construction des immeubles de grande hauteur et leur protection contre les risques d'incendie et de panique; Section VIII; Article GH 48, Eclairage) Glow-wire test for outer parts of luminaires:		N/A
	- 850°C for luminaires in stairways and horizontal travel paths		N/A
	- 650°C for indoor luminaires		N/A
	GB: Requirements according to United Kingdom Building Regulation		N/A

Attachment No.2

BS EN IEC 62031

Clause	Requirement + Test	Result - Remark	Verdict
13 (14)	FAULT CONDITIONS		P
- (14.1)	In compliance with IEC 61347-1 (clause numbers between parentheses refer to IEC 61347-1)		N/A
	When operated under fault conditions the LED module:		N/A
	- does not emit flames or molten material		N/A
	- does not produce flammable gases		N/A
	- protection against accidental contact not impaired		N/A
	Thermally protected controlgear does not exceed the marked temperature value		N/A
	Fault conditions: capacitors, resistors or inductors without proof of compliance with relevant specifications have been short-circuited or disconnected		N/A
- (14.2)	Short-circuit of creepage distances and clearances if less than specified in clause 16 in Part 1 (except between live parts and accessible metal parts)		N/A
	Creepage distances on printed boards less than specified in clause 16 in Part 1 provided with coating according to IEC 60664- 3		N/A
- (14.3)	Short-circuit or interruption of semiconductor devices		N/A
- (14.4)	Short-circuit across insulation consisting of lacquer, enamel or textile		N/A
- (14.5)	Short-circuit across electrolytic capacitors		N/A
- (14.6)	After the tests has been carried out on three samples:		N/A
	The insulation resistance $\geq 1 \text{ M}\Omega$		N/A
	No flammable gases		N/A
	No accessible parts have become live		N/A
	During the tests, a five-layer tissue paper, where the test specimen is wrapped, does not ignite		N/A
- (14.7)	Relevant fault condition tests with high-power supply		N/A
13.2	Overpower condition		P
	Module withstands overpower condition >15 min.		P
	Module with automatic protective device or power limiter, test performed 15 min. at limit.		N/A
	No fire, smoke or flammable gas is produced		P
	Molten material does not ignite tissue paper, spread below the module		P

Attachment No.3

IEC TR 62778


Clause	Requirement + Test			Result - Remark					Verdict
Table 6.1	Emission limits for risk groups of continuous wave lamps (based on EU Directive 2006/25/EC)								—
	Photobiological safety of lamps and lamp systems (LED bulb emit white light)								P
Risk	Action spectrum m	Symb ol	Units	Emission limits					
				Exempt	Result	Low risk	Result	Mod risk	Result
Actinic UV	S _{UV} (λ)	E _s	mW·m ⁻²	0,001	1.002E-06	0.003	--	--	--
Near UV	--	E _{UVA}	W·m ⁻²	0,33	3.455E-04	33	--	--	--
Blue light	B(λ)	L _B	W·m ⁻² ·sr ⁻¹	100	3.087E+00	10000	--	4000000	--
Blue light, small source	B(λ)	E _B	W·m ⁻²	1,0*	--	--	--	400	--
Retinal thermal	R(λ)	L _R	W·m ⁻² ·sr ⁻¹	28000/α	1.006E+03	1.011E+06	--	71000/α	--
Retinal thermal, weak visual stimulus**	R(λ)	L _{IR}	W·m ⁻² ·sr ⁻¹	545000 0,0017≤ α ≤ 0,011	--				
					--				
IR radiation, eye	--	E _{IR}	W·m ⁻²	6000/α 0,011≤ α ≤ 0,1	0.000E+00	570	--	3200	--
* Small source defined as one with α < 0,011radian. Averaging field of view at 10000 s is 0.1radian. ** Involves evaluation of non-GLS source NOTE 1. Angular subtense of apparent source: α=77.53 mrad 2. Measure distance is 200mm.									
Blue light	B(λ)	LB	W·m ⁻² ·sr ⁻¹	100	3.746E+00	10000	--	4000000	--
NOTE Angular subtense of apparent source: α= 77.53 mrad. Measure distance 200mm.									



Attachment No.4**Product Photos**



Details of: Fig. 1





Details of: Fig. 2



Attachment No.4**Product Photos**Details of: Fig. 3Details of: Fig. 4


Attachment No.4**Product Photos**Details of: Fig. 5Details of: Fig. 6

Attachment No.4**Product Photos**Details of: Fig. 7Details of: Fig. 8

Attachment No.4

Product Photos

Details of: Fig. 9



Details of: Fig. 10



- End of test report -